

1200-Mini SERIES PRESSURE REDUCING REGULATORS



1250-M



1260-M

THE 1200-Mini SERIES REGULATORS ARE ADJUSTABLE SINGLE STAGE PRESSURE REDUCING REGULATORS. THESE SINGLE STAGE DESIGNS PROVIDES STABLE OUTLET PRESSURE WITH RESPECT TO THE REDUCING INLET PRESSURE.

Materials of constructions ...

| | |
|--------------|---|
| Body | Stainless Steel 303 |
| Gauge | Stainless Steel 316 (1260-M) , Brass (1250-M) |
| Lock Nut | Brass NP |
| Valve Seat | PCTFE |
| Seals | Viton |
| Diaphragm | SS316 |
| Control Knob | Aluminum Anodized |
| Valve spring | SS316 |

| Model | Maximum Inlet Pressure | For Reactive gases or Non-reactive gases | Inlet Connection | Outlet Connection | Inlet Gauge | Weight Kg |
|---------------|---------------------------|--|------------------|---------------------|---|-----------|
| 1250-M | 0 to 1200 psig/ 83 bar | Brass NP- For Non-Reactive Gases | 5/8"x18 UN-C10 | 3/16" Barb 4.8mm | Brass 0 to 1500psig 103 bar | 0.380 Kg |
| 1260-M | 0 to 1200 psig/ 83 bar | Stainless Steel for Reactive Gases | 5/8"x18 UN-C10 | 3/16" Barb 4.8mm | Stainless Steel 0 to 1500psig 103 bar | 0.380 kg |

Outlet pressure options for all the variants

| Outlet pressure | Outlet pressure gauge |
|-----------------|-----------------------|
| 0 to 1 bar | 0 to 2 bar |
| 0 to 4 bar | 0 to 7 bar |
| 0 to 7 bar | 0 to 10 bar |

Warranty

All regulators are warranted for 12 months